



Canopy Application Warning: Restrictions exist on weight, center of gravity (C.G.), and Frontal Area for all Chassis Cab or Pickup Box Delete incomplete vehicles. There are additional restrictions for those vehicles rated 10,000 GVWR or less. Extreme care must be taken when determining whether a specific canopy and service body can be installed. Availability of a canopy and service body that will fit a specific Chassis Cab or Pickup Box Delete does not mean it will comply with the chassis manufacturer's limitations. Refer to specific trucks limitations, shown in the truck manufacturer's Incomplete Vehicle Manual (IVM), before making a selection.

Canopies are furnished standard with a stationary roof enclosing load area. One (1) glass in front panel and one (1) in each rear door panel. Standard shelving consists of one full length shelf and a retainer lip at body compartment top to provide two (2) full length shelves each side. Rear doors are double overlapping to provide full load area access.

Canopies are factory installed options only and body tailgate is omitted.

For alternative latch options, request T-Handle, D-Ring, or Rotary latch at time of order.



Application	Model	Length (in)	Load Area Width (in)	Height from Floor (in)	Height From Top of Compartment (in)	Approximate Weight (lbs.)
L56D94	CTL56D945	96	65	55	31	703
L56D94	CTL56D946	96	65	60	36	743
L56DW94	CTL56DW945	96	54	55	31	674
L56DW94	CTL56DW946	96	54	60	36	714
L5680	CTL56806	96	51	60	36	665
S56D94	CTS56D945	96	65	55	26	663
S56D94	CTS56D946	96	65	60	31	703
S56DW94	CTS56DW945	96	54	55	26	634
S56DW94	CTS56DW946	96	54	60	31	674
E60D89	CTE60D895	108	60	55	28	658
E60D89	CTE60D896	108	60	60	33	699
E60D94	CTE60D945	108	65	55	28	700
E60D94	CTE60D946	108	65	60	33	742
E60DW89	CTE60DW895	108	49	55	28	739
E60DW89	CTE60DW896	108	49	60	33	780
E60DW94	CTE60DW945	108	54	55	28	719
E60DW94	CTE60DW946	108	54	60	33	761
L60D89	CTL60D895	108	60	55	31	683
L60D89	CTL60D896	108	60	60	36	724
L60D94	CTL60D945	108	65	55	31	759
L60D94	CTL60D946	108	65	60	36	801
L60DW89	CTL60DW895	108	49	55	31	764
L60DW89	CTL60DW896	108	49	60	36	805
L60DW94	CTL60DW945	108	54	55	31	778
L60DW94	CTL60DW946	108	54	60	36	820
L6080	CTL60806	108	51	60	36	708
S60D89	CTS60D895	108	60	55	26	642
S60D89	CTS60D896	108	60	60	31	683
S60D94	CTS60D945	108	65	55	26	717
S60D94	CTS60D946	108	65	60	31	759
S60DW89	CTS60DW895	108	49	55	26	723
S60DW89	CTS60DW896	108	49	60	31	764
S60DW94	CTS60DW945	108	54	55	26	736
S60DW94	CTS60DW946	108	54	60	31	778
E84D89	CTE84D895	132	60	55	28	786
E84D89	CTE84D896	132	60	60	33	842
E84D89	CTE84D897	132	60	72	45	976
E84D94	CTE84D945	132	65	55	28	802
E84D94	CTE84D946	132	65	60	33	849
E84D94	CTE84D947	132	65	72	45	1,015
E84DW89	CTE84DW895	132	49	55	28	784



Application	Model	Length (in)	Load Area Width (in)	Height from Floor (in)	Height From Top of Compartment (in)	Approximate Weight (lbs.)
E84DW89	CTE84DW896	132	49	60	33	839
E84DW89	CTE84DW897	132	49	72	45	971
E84DW94	CTE84DW945	132	54	55	28	787
E84DW94	CTE84DW946	132	54	60	33	834
E84DW94	CTE84DW947	132	54	72	45	1,010
L84D89	CTL84D895	132	60	55	31	830
L84D89	CTL84D896	132	60	60	36	876
L84D89	CTL84D897	132	60	72	48	1,003
L84D94	CTL84D945	132	65	55	31	868
L84D94	CTL84D946	132	65	60	36	915
L84D94	CTL84D947	132	65	72	48	1,045
L84DW89	CTL84DW895	132	49	55	31	839
L84DW89	CTL84DW896	132	49	60	36	885
L84DW89	CTL84DW897	132	49	72	48	1,015
L84DW94	CTL84DW945	132	54	55	31	853
L84DW94	CTL84DW946	132	54	60	36	900
L84DW94	CTL84DW947	132	54	72	48	1,030
S84D89	CTS84D895	132	60	55	26	784
S84D89	CTS84D896	132	60	60	31	830
S84D89	CTS84D897	132	60	72	43	957
S84D94	CTS84D945	132	65	55	26	821
S84D94	CTS84D946	132	65	60	31	868
S84D94	CTS84D947	132	65	72	43	998
S84DW89	CTS84DW895	132	49	55	26	793
S84DW89	CTS84DW896	132	49	60	31	839
S84DW89	CTS84DW897	132	49	72	43	966
S84DW94	CTS84DW945	132	54	55	26	806
S84DW94	CTS84DW946	132	54	60	31	853
S84DW94	CTS84DW947	132	54	72	43	983
E102DW94	CTE102DW945	144	54	55	28	821
E102DW94	CTE102DW946	144	54	60	33	871
E102DW94	CTE102DW947	144	54	72	45	993
E108DW94	CTE108DW945	156	54	55	28	855
E108DW94	CTE108DW946	156	54	60	33	1,175
E108DW94	CTE108DW947	156	54	72	45	1,035
L108DW94	CTL108DW945	156	54	55	31	920
L108DW94	CTL108DW946	156	54	60	36	971
L108DW94	CTL108DW947	156	54	72	48	1,111
S108DW94	CTS108DW945	156	54	55	26	845
S108DW94	CTS108DW946	156	54	60	31	892
S108DW94	CTS108DW947	156	54	72	43	1,028
E120DW94	CTE120DW945	168	54	55	28	941



Application	Model	Length (in)	Load Area Width (in)	Height from Floor (in)	Height From Top of Compartment (in)	Approximate Weight (lbs.)
E120DW94	CTE120DW946	168	54	60	33	993
E120DW94	CTE120DW947	168	54	72	45	1,139
L120DW94	CTL120DW945	168	54	55	31	1,012
L120DW94	CTL120DW946	168	54	60	36	1,068
L120DW94	CTL120DW947	168	54	72	48	1,225
S120DW94	CTS120DW945	168	54	55	26	929
S120DW94	CTS120DW946	168	54	60	31	983
S120DW94	CTS120DW947	168	54	72	43	1,132